

PATENT ABSTRACTS OF JAPAN

(11)Publication number : 2002-043991
(43)Date of publication of application : 08.02.2002

(51)Int.Cl. H04B 7/005
H04B 3/10
H04B 7/26
H04J 13/00
H04L 27/38
H04L 27/01
H04L 27/22

(21)Application number : 2000-225161 (71)Applicant : MATSUSHITA ELECTRIC IND CO LTD
(22)Date of filing : 26.07.2000 (72)Inventor : MIYOSHI KENICHI
UESUGI MITSURU

(54) WIRELESS RECEIVING DEVICE AND WIRELESS RECEIVING METHOD

(57)Abstract:

PROBLEM TO BE SOLVED: To provide a wireless receiving device that can estimate a channel with high accuracy by preventing the accuracy of channel estimate from being deteriorated when a channel is estimated by using a signal whose data part is not known.

SOLUTION: A likelihood calculation section 205 calculates likelihood of a data part signal and outputs a weight coefficient in response to the likelihood to a multiplier 206, the multiplier 206 multiplies a weight coefficient outputted from the likelihood-calculation section 205 b a data channel estimate value outputted from a data channel estimate section 204 to apply weighting to the data channel estimate value depending on the likelihood of the data part signal, and a synthesis section 207 synthesizes the PL(pilot) channel estimate value with the data channel estimate value weighted depending on the likelihood of the data part signal to obtain a final channel estimate value.

